



LED A19-A21

16A21/PER/950/P/E26/DIM 6/1FB T20

Philips A19/A21 LED lamps are the smart alternative to standard incandescent. The unique lamp design provides omni-directional light with excellent dimming performance.

Product data


General Information	
Cap-Base	E26 [Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	16-100W
Light Technical	
Color Code	950 [CCT of 5000K]
Beam Angle (Nom)	250 °
Luminous Flux (Nom)	1600 lm
Color Designation	Daylight
Correlated Color Temperature (Nom)	5000 K
Luminous Efficacy (rated) (Nom)	100.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	60 Hz
Power (Nom)	16 W
Lamp Current (Nom)	145 mA
Wattage Equivalent	100 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	90 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Approval and Application	
Energy Efficiency Label (EEL)	Not applicable
Energy Consumption kWh/1000 h	- kWh
Product Data	
Order product name	16A21/PER/950/P/E26/DIM 6/1FB T20
EAN/UPC - Product	046677550523
Order code	929002037104
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002037104

LED A19-A21

Net Weight (Piece)	0.174 kg
--------------------	----------


Dimensional drawing




A21 120V 17.7-100W 1600lm 5000K E26 D

Product	D	C
16A21/PER/950/P/E26/DIM 6/1FB T20	78 mm	140 mm


Photometric data



100W E26 A21 950 Frosted



40 60 75 100W E26 A19 A21 Frosted




General Parameters (1) Page Lighting (1) Page 11

100W E26 A21 950 Frosted

LED A19-A21

Lifetime



15K LED

15K LMP

